

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011

Daraset 300

No.: GRALAR-Ap32-01

1. Unique identification code of the product-type:

EN 934-2 T6

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch No. see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Set accelerating admixture for concrete

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Grace Produits de Constructions S.A.S. ZA Les Foulletons 39140 Larnaud FRANCE

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body CERIB, identification number 1164, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued a certificate of conformity of the factory production control 1164-CPD-ADJ007

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant



9. Declared performance

	Essential characteristics	Performance	Harmonised Technical specification
	Chloride ion content	max. 0,10% by mass	
	Alkali content	max. 5,00% by mass	
	Corrosion behaviour	Contains the following components from EN 934-1:2008 Annex A.2:Nitrate, Nitrite, Thiocyanate	
	Dangerous substances	NPD	
Т6	Air content	Test mix ≤ 2 % by volume above control mix	EN 934-2:2009 +A1:2012
	Compressive strength	At 28 days: Test mix ≥ 80 % control mix At 90 days: Test mix ≥ test mix at 28 days	
	Initial setting time	At 20° C: test mix ≥ 30 min At 5° C: test mix ≤ 60 % of control mix	

NPD=No performance determined

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Gérard BLOND General Manager (place and date of issue) 28/06/2013

(signature)